

.223 Rem. SWISS P AP


4.1 g / 63 gr

The most accurate Armour Piercing round

The tungsten carbide core provides outstanding penetration power

Extended barrel durability due to patented Projectile design

Coordinated ballistics with SWISS P Ball, Target, Styx Action and Tactical round



Cartridge	5.56×45 / .223 Rem.	
Projectile	AP, 4.1 g/63 gr	
Projectile material	tombac jacket, tungsten carbide & lead cores	
Ballistic coefficient G1	0.3632 (ICAO)	
Primer	SINOXID	
Case material	CuZn – alloy	
Cartridge weight	12.2 g	
Performance		
Term of reference	C.I.P.	
Mean chamber pressure	max. 4300 bar	(21 °C)
Mean muzzle velocity	875 ± 15 m/s (2870 ± 49 fps)	500 mm barrel
Mean muzzle energy (Min–Max)	1570 J (1516–1624 J)	
Accuracy at 300 m	$s_a \leq 25$ mm	650 mm barrel
Penetration at 200 m	5 mm steel plate, 480–530HB	
Packaging		
Standard cardboard box	10rds/clip, 50rds/cardboard box, 200rds/SLD-PVC, 1000rds/cardboard box, 50000rds EU pallet	

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products. All information and specifications shown in factsheets are non-binding and subject to alterations without prior notice at any time. 01.2023

SwissP Defence AG | info@swiss-p.com | www.swiss-p.com

SWISS 
The Sniper's Choice