

.223 Rem. SWISS P Styx Action

4.5 g / 69 gr

Outstanding stopping power while eliminating the risk of collateral damage

Match grade accuracy

Coordinated ballistics with SWISS P Ball, Target and Armour Piercing rounds

Optional with heavy metal free ignition



| | | |
|------------------------------|--|--------------|
| Cartridge | 5.56×45 / .223 Rem. | |
| Projectile | JHP, 4.5g/69gr | |
| Projectile material | tombac jacket, lead core | |
| Ballistic coefficient G1 | 0.3614 (ICAO) | |
| Primer/optional | SINOXID/SINTOX® – non toxic | |
| Case material | CuZn – alloy | |
| Cartridge weight | 12.6g | |
| Performance | | |
| Term of reference | C.I.P. | |
| Mean chamber pressure | max. 4300bar | (21 °C) |
| Mean muzzle velocity | 895 ± 15m/s (2936 ± 49fps) | 600mm barrel |
| Mean muzzle energy (Min–Max) | 1802J (1742–1863J) | |
| Accuracy at 300m | s _a ≤ 16.9mm | 650mm barrel |
| Packaging | | |
| Standard cardboard box | 10rds/clip, 50rds/cardboard box, 200rds/SLD-PVC, 1000rds/cardboard box, 50000rds EU pallet | |
| Military M2A1 metal box | 10rds/clip, 50rds/ cardboard box, 1000rds/M2A1 metal box, 60000rds EU pallet | |

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products. All information and specifications shown in factsheets are non-binding and subject to alterations without prior notice at any time. 01.2023

SwissP Defence AG | info@swiss-p.com | www.swiss-p.com

SWISS 
The Sniper's Choice