

# .223 Rem. SWISS P Target

## 4.5 g/69 gr

The most accurate .223 Rem. round

Enhanced operating range of up to 600 m

Preserves the weapon's service life

Coordinated ballistics with SWISS P Ball, Styx Action and Armour Piercing rounds

Optional with heavy metal free ignition



Cartridge	5.56×45/ .223 Rem.	
Projectile	HPBT, 4.5 g/69 gr	
Projectile material	tombac jacket, lead core	
Ballistic coefficient G1	0.3934 (ICAO)	
Primer/optional	SINOXID/SINTOX® – non toxic	
Case material	CuZn – alloy	
Cartridge weight	12.6 g	
Performance		
Term of reference	C.I.P.	
Mean chamber pressure	max. 4300 bar	(21 °C)
Mean muzzle velocity	895 ± 15 m/s (2936 ± 49 fps)	600 mm barrel
Mean muzzle energy (Min–Max)	1802 J (1742 – 1863 J)	
Accuracy at 300 m	$s_a \leq 16.9$ mm	650 mm barrel
Packaging		
Standard cardboard box	10rds/clip, 50rds/cardboard box, 200rds/SLD-PVC, 1000rds/cardboard box, 50000rds EU pallet	
Military M2A1 metal box	10rds/clip, 50rds/ cardboard box, 1000rds/M2A1 metal box, 60000rds EU pallet	

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products. All information and specifications shown in factsheets are non-binding and subject to alterations without prior notice at any time. 01.2023

SwissP Defence AG | info@swiss-p.com | www.swiss-p.com

**SWISS**   
The Sniper's Choice