

# .308 Win. SWISS P Subsonic Final

## 13.0 g / 200 gr

Outstanding stopping power avoids collateral damage due to total bullet disintegration

Provides a minimal acoustic profile to maintain the element of surprise

Best first hit probability due to a special loading technique



<b>Cartridge</b>	<b>7.62×51 / .308 Win.</b>
Projectile	JPP, 13.0g/200gr
Projectile material	tin plated tombac jacket, pressed lead pellets
Ballistic coefficient G1	0.1587 (ICAO)
Primer	SINOXID
Case material	CuZn – alloy
Cartridge weight	27.0g

<b>Performance</b>		
Term of reference	C.I.P.	
Mean chamber pressure	max. 3 600 bar	(21 °C)
Mean muzzle velocity	310 ± 10 m/s (1 017 ± 33 fps)	450 mm barrel with suppressor
Mean muzzle energy (Min–Max)	625 J (585–666 J)	
Accuracy at 50 m	100 % radius ≤ 30 mm	

<b>Packaging</b>	
Standard cardboard box	20rds / cardboard box, 200rds / cardboard box, 10 000rds EU pallet
Military M2A1 metal box	10rds / cardboard box, 400rds / M2A1 metal box, 24 000rds EU pallet

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products. All information and specifications shown in factsheets are non-binding and subject to alterations without prior notice at any time. 01.2023

SwissP Defence AG | info@swiss-p.com | www.swiss-p.com

**SWISS**   
The Sniper's Choice